Oria tubing sourced from Mannesman Steel Works, the same company that Columbus.

Oria KK - 1,880g (similar to Columbus Max) _Triple butted
Oria ML34 - 1,880g
Oria GM 0.0 - 1,940g _Double butted
Oria RANF - 1,990g (similar to Columbus SLX/TSX) _Double butted
Oria ML 25 - 2,080g
Oria TT (similar to Columbus Aelle)

Oria Tubing Specs

	TubeSet	Top Tube		Down Tube		Seat Tube		Seat Stay		Chain Stay		Fork Leg		Steerer Tube		Weight Per Set [kg]
		Diameter	Wall	Diameter	Wall	Diameter	Wall	Diameter	Wall	Diameter	Wall	Diameter	Wall	Diameter	Wall	
ORIA	HI Tension	25.4	0.8	28.6	0.8	28.6	0.8	14	0.85	22.2	0.85	24	1	25.4	--	2.230
	HI-Ten Oversize	28.6	1	31.7	1	28.6	1	16	1	22.2	1.2	25.4	1.3	25.4	--	2.850
	CroMoly	25.4	0.8	28.6	0.8	28.6	0.8	14	0.8	22.2	0.8	24	1	25.4	--	2.190
	Ml 25	25.4	0.7	28.6	0.8	28.6	0.7	14	0.8	22.2	0.8	24	1	25.4	--	2.080
	ML 34	25.6	0.55	28.6	0.65	28.6	0.65	14	0.77	22.2	0.7	24	0.9	25.4	--	1.880
	RANF	25.4	0.95 / 0.75	28.6	0.95 / 0.85	28.6	0.7 / 0.55	14	0.8 / 0.7	22.2	0.9 / 0.8	24	1	25.4	--	1.990
	GM 00	25.4	0.85 / 0.7	28.6	0.85 / 0.7	28.6	0.75 / 0.55	14	0.75	22.2	0.75	24	0.95	25.4	--	1.940
	Double butted	25.4	0.85 / 0.7	28.6	0.9 / 0.65	28.6	0.85 / 0.65	14	0.75	22.2	0.75	24	0.95	25.4	--	2.000
	KK	28.6	0.8 / 0.75 / 0.7	31.7	0.8 / 0.75 / 0.7	28.6	0.65	14	0.7	22.2	0.7	24	0.9	25.4	--	1.880
	CroMoly-Oversize	28.6	1	31.7	1	28.6	0.8	16	1	22.2	1.2	25.4	1.3	25.4	--	--
	SGM 00	28.6	1 / 0, 9	31.7	1 / 0, 9	28.6	0.8 / 0.7	16	0.95	22.2	1.1	25.4	1.2	25.4	--	2.720
	Top	28.6	1	31.7	1	28.6	0.8	16	1	22.2	1.2	25.4	1.3	25.4	--	2.860
	Oversize	31.7	0.8	34.9	0.8	31.7	0.8	19	0.8	24	1	28.6	1.2	28.6	--	2.690
	Over Double	31.7	1 / 0, 8 / 1	34.9	0.9 / 0.7 / 0.9	31.7	1 / 0, 7 / 1	--	0.8	24	1	28.6	1.2	28.6	--	2.650
	Butted Top	31.7	0.8	34.9	0.8	31.7	0.8	19	0.8	24	1	28.6	1.2	28.6	--	2.690
	CSS 52	25.4	0.8	28.6	0.8	28.6	0.8	14	0.85	22.2	1	24	1	25.4	--	2.230