



Basis Geometrie

	2XS	XS	S	M	L	XL	2XL
KÖRPERGRÖSSE IN CM	< 166	166 - 172	172 - 178	178 - 184	184 - 190	190 - 196	> 196
SITZHÖHE IN MM (A)	624 - 724	654 - 754	684 - 784	714 - 814	744 - 844	774 - 874	804 - 904
SITZROHRLÄNGE IN MM (B)	420	450	480	510	540	570	600
OBERROHRLÄNGE IN MM (C)	516	529	546	555	569	594	610
STEUERROHR IN MM (D)	115	107	121	142	162	188	206
LENKWINKEL (E)	71,5°	71,2°	72,8°	73,3°	73,3°	73,5°	73,8°
SITZROHRWINKEL (F)	73,9°	73,9°	73,9°	73,9°	73,9°	73,9°	73,9°
KETTENSTREBEN IN MM (G)	405	410	410	410	413	415	415
RADSTAND IN MM (H)	965	979	982	988	1.003	1.029	1.042
STACK IN MM (I)	498	520	539	560	580	606	624
REACH IN MM (J)	372	378	390	393	401	419	429
ÜBERSTANDSHÖHE IN MM (K)	720	748	775	801	828	851	874
TRETLAGER-OFFSET IN MM (L)	60	73	73	73	73	73	73
STACK+ IN MM	572	596	613	635	656	681	701
REACH+ IN MM	430	446	459	473	490	509	530

Dimensionen Anbauteile

	2XS	XS	S	M	L	XL	2XL
SPACER IN MM	15,0	15,0	15,0	15,0	15,0	15,0	15,0
MASSE DES COCKPITS	80-390	90-390	90-390	100-410	110-410	110-410	120-410
KURBELLÄNGE IN MM	170,0	170,0	172,5	172,5	175,0	175,0	175,0
KETTENBLATTGRÖSSE	52/36	52/36	52/36	52/36	52/36	52/36	52/36
SATTELSTÜTZE Ø IN MM	27,2	27,2	27,2	27,2	27,2	27,2	27,2
SATTELSTÜTZENLÄNGE IN MM	316	316	316	316	316	316	316
MAXIMALE EINSCHUBTIEFE DER SATTELSTÜTZE IN MM	160	160	160	160	160	160	160
MINIMALE EINSCHUBTIEFE DER SATTELSTÜTZE IN MM	60	60	60	60	60	60	60
LAUFRADGRÖSSE	28"	28"	28"	28"	28"	28"	28"
DURCHMESSER BREMSSCHEIBE IN MM	140 / 140	140 / 140	160 / 140	160 / 140	160 / 140	160 / 160	160 / 160